

isc Silicon PNP Power Transistor

2SA1552

DESCRIPTION


- High voltage and large current capacity
- Ultrahigh-speed switching
- Small and slim package permitting
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation
- Complementary to 2SC4027

APPLICATIONS

- Converters , inverters and color TV audio output

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	-180	V
V_{CEO}	Collector-Emitter Voltage	-160	V
V_{EBO}	Emitter-Base Voltage	-6	V
I_C	Collector Current-Continuous	-1.5	A
I_{CM}	Collector Current-Peak	-2.5	A
P_C	Collector Power Dissipation @ $T_C=25^{\circ}\text{C}$	15	W
	Collector Power Dissipation @ $T_a=25^{\circ}\text{C}$	1.0	
T_J	Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^{\circ}\text{C}$



isc Silicon PNP Power Transistor**2SA1552****ELECTRICAL CHARACTERISTICS****T_c=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = -0.5A; I _B = -50mA			-0.5	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = -0.5A; I _B = -50mA			-1.2	V
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	I _C = -10μA; I _B = 0	-180			V
V _{(BR)EBO}	Emitter-Base Breakdown Voltage	I _E = -10μA; I _C = 0	-6			V
I _{CBO}	Collector Cutoff Current	V _{CB} = -120V; I _E = 0			-1.0	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = -4V; I _C = 0			-1.0	μ A
h _{FE-1}	DC Current Gain	I _C = -0.1A; V _{CE} = -5V	100		400	
h _{FE-2}	DC Current Gain	I _C = -10mA; V _{CE} = -5V	80			
C _{OB}	Output Capacitance	I _E = 0; V _{CB} = -10V; f= 1.0MHz		22		pF
f _T	Current-Gain—Bandwidth Product	I _C = -50mA; V _{CE} = -10V		120		MHz

◆ h_{FE-1} Classifications

R	S	T
100-200	140-280	200-400

isc Silicon PNP Power Transistor

2SA1552

Outline Drawing

