

Dual Enhancement Mode MOSFET (N-and P-Channel)


Features

- N-Channel
30V/5A,
 $R_{DS(ON)} = 35m\Omega (typ.) @ V_{GS} = 10V$
 $R_{DS(ON)} = 45m\Omega (typ.) @ V_{GS} = 4.5V$
- P-Channel
-30V/-5A,
 $R_{DS(ON)} = 40m\Omega (typ.) @ V_{GS} = -10V$
 $R_{DS(ON)} = 55m\Omega (typ.) @ V_{GS} = -4.5V$
- Super High Dense Cell Design
- Reliable and Rugged
- Lead Free Available (RoHS Compliant)


Applications

- Power Management in Notebook Computer,
Portable Equipment and Battery Powered
Systems

Pin Description



Top View of SOP – 8



N-Channel MOSFET P-Channel MOSFET

Ordering and Marking Information

APM4536 □□-□□□ □□-□□□ Lead Free Code □□-□□□ Handling Code □□-□□□ Temp. Range □□-□□□ Package Code	Package Code K : SOP-8 Operating Junction Temp. Range C : -55 to 150°C Handling Code TU : Tube TR : Tape & Reel Lead Free Code L : Lead Free Device Blank : Original Device
APM4536 K : APM4536 XXXXX	XXXXXX - Date Code

Note: ANPEC lead-free products contain molding compounds/die attach materials and 100% matte in plate termination finish; which are fully compliant with RoHS and compatible with both SnPb and lead-free soldering operations. ANPEC lead-free products meet or exceed the lead-free requirements of IPC/JEDEC J STD-020C for MSL classification at lead-free peak reflow temperature.

ANPEC reserves the right to make changes to improve reliability or manufacturability without notice, and advise customers to obtain the latest version of relevant information to verify before placing orders.

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter		N Channel	P Channel	Unit
V _{DSS}	Drain-Source Voltage		30	-30	V
V _{GSS}	Gate-Source Voltage		±16	±16	
I _D *	Continuous Drain Current	V _{GS} =±10V	5	-5	A
I _{DM} *	Pulsed Drain Current		20	-20	
I _S *	Diode Continuous Forward Current		1.7	-1.7	A
T _J	Maximum Junction Temperature		150		°C
T _{STG}	Storage Temperature Range		-55 to 150		
P _D *	Power Dissipation	T _A =25°C	2		W
		T _A =100°C	0.8		
R _{θJA} *	Thermal Resistance-Junction to Ambient		62.5		°C/W

Note:

*Surface Mounted on 1in^2 pad area, $t \leq 10\text{sec}$.
Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Condition	APM4536K			Unit	
			Min.	Typ.	Max.		
Static Characteristics							
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	N-Ch	30			V
		V _{GS} =0V, I _{DS} =-250μA	P-Ch	-30			
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =24V, V _{GS} =0V	N-Ch			1	μA
		T _J =85°C				30	
		V _{DS} =-24V, V _{GS} =0V	P-Ch			-1	
		T _J =85°C				-30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	N-Ch	0.7	1.1	1.5	V
		V _{DS} =V _{GS} , I _{DS} =-250μA	P-Ch	-1	-1.5	-2	
I _{GSS}	Gate Leakage Current	V _{GS} =±16V, V _{DS} =0V	N-Ch			±100	nA
			P-Ch			±100	
R _{DS(ON)} ^a	Drain-Source On-State Resistance	V _{GS} =10V, I _{DS} =5A	N-Ch		35	50	mΩ
		V _{GS} =-10V, I _{DS} =-5A	P-Ch		40	55	
		V _{GS} =4.5V, I _{DS} =4A	N-Ch		45	60	
		V _{GS} =-4.5V, I _{DS} =-4A	P-Ch		55	75	

Electrical Characteristics (Cont.) (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	APM4536K			Unit	
			Min.	Typ.	Max.		
Diode Characteristics							
V _{SD} ^a	Diode Forward Voltage	I _{SD} =1.7A , V _{GS} =0V	N-Ch		0.8	1.3	V
		I _{SD} =-1.7A , V _{GS} =0V	P-Ch		-0.8	-1.3	
Dynamic Characteristics ^b							
R _G	Gate Resistance	V _{GS} =0V,V _{DS} =0V,F=1MHz	N-Ch		3		Ω
			P-Ch		12		
C _{iss}	Input Capacitance	N-Channel V _{GS} =0V, V _{DS} =25V, Frequency=1.0MHz	N-Ch		360		pF
C _{oss}	Output Capacitance		P-Ch		650		
			N-Ch		75		
C _{rss}	Reverse Transfer Capacitance		P-Ch		145		
		N-Ch		35			
t _{d(ON)}	Turn-on Delay Time	N-Channel V _{DD} =15V, R _L =15Ω, I _{DS} =1A, V _{GEN} =10V, R _G =6Ω	P-Ch		80		
			N-Ch		10	15	
T _r	Turn-on Rise Time		P-Ch		10	20	
			N-Ch		8	20	
t _{d(OFF)}	Turn-off Delay Time	P-Channel V _{DD} =-15V, R _L =15Ω, I _{DS} =-1A, V _{GEN} =-10V, R _G =6Ω	P-Ch		15	30	ns
			N-Ch		20	28	
T _f	Turn-off Fall Time		P-Ch		25	50	
			N-Ch		5	15	
			P-Ch		15	30	
Gate Charge Characteristics ^b							
Q _g	Total Gate Charge	N-Channel V _{DS} =15V, V _{GS} =10V, I _{DS} =5A	N-Ch		14.5	20	
			P-Ch		26	35	
Q _{gs}	Gate-Source Charge	P-Channel V _{DS} =-15V, V _{GS} =-10V, I _{DS} =-5A	N-Ch		4.3		nC
			P-Ch		5.1		
Q _{gd}	Gate-Drain Charge		N-Ch		2.3		
			P-Ch		3.3		

Notes:


a : Pulse test ; pulse width≤300μs, duty cycle≤2%.

b : Guaranteed by design, not subject to production testing.


Typical Characteristics

N-Channel


Power Dissipation




Drain Current



Safe Operation Area




Thermal Transient Impedance




Typical Characteristics (Cont.)

N-Channel


Output Characteristics




Drain-Source On Resistance



Transfer Characteristics




Gate Threshold Voltage




Typical Characteristics (Cont.)

N-Channel


Drain-Source On Resistance




Source-Drain Diode Forward



Capacitance




Gate Charge




Typical Characteristics (Cont.)

P-Channel


Power Dissipation




Drain Current



Safe Operation Area




Thermal Transient Impedance




Typical Characteristics (Cont.)

P-Channel


Output Characteristics




Drain-Source On Resistance



Transfer Characteristics




Gate Threshold Voltage




Typical Characteristics (Cont.)

P-Channel


Drain-Source On Resistance




Source-Drain Diode Forward



Capacitance




Gate Charge



Packaging Information

SOP-8 pin (Reference JEDEC Registration MS-012)




Dim	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	1.35	1.75	0.053	0.069
A1	0.10	0.25	0.004	0.010
D	4.80	5.00	0.189	0.197
E	3.80	4.00	0.150	0.157
H	5.80	6.20	0.228	0.244
L	0.40	1.27	0.016	0.050
e1	0.33	0.51	0.013	0.020
e2	1.27BSC		0.50BSC	
$\phi 1$	8°		8°	

Physical Specifications

Terminal Material	Solder-Plated Copper (Solder Material : 90/10 or 63/37 SnPb), 100%Sn
Lead Solderability	Meets EIA Specification RSI86-91, ANSI/J-STD-002 Category 3.

Reflow Condition (IR/Convection or VPR Reflow)



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	3°C/second max.	3°C/second max.
Preheat - Temperature Min (T_{smin}) - Temperature Max (T_{smax}) - Time (min to max) (t_s)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: - Temperature (T_L) - Time (t_L)	183°C 60-150 seconds	217°C 60-150 seconds
Peak/Classification Temperature (T_p)	See table 1	See table 2
Time within 5°C of actual Peak Temperature (t_p)	10-30 seconds	20-40 seconds
Ramp-down Rate	6°C/second max.	6°C/second max.
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.

Notes: All temperatures refer to topside of the package .Measured on the body surface.

Classificatin Reflow Profiles(Cont.)

Table 1. SnPb Entectic Process – Package Peak Reflow Temperatures

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	240 +0/-5°C	225 +0/-5°C
≥2.5 mm	225 +0/-5°C	225 +0/-5°C

Table 2. Pb-free Process – Package Classification Reflow Temperatures


Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
<1.6 mm	260 +0°C*	260 +0°C*	260 +0°C*
1.6 mm – 2.5 mm	260 +0°C*	250 +0°C*	245 +0°C*
≥2.5 mm	250 +0°C*	245 +0°C*	245 +0°C*

*Tolerance: The device manufacturer/supplier **shall** assure process compatibility up to and including the stated classification temperature (this means Peak reflow temperature +0°C. For example 260°C+0°C) at the rated MSL level.


Reliability Test Program

Test item	Method	Description
SOLDERABILITY	MIL-STD-883D-2003	245°C, 5 SEC
HOLT	MIL-STD 883D-1005.7	1000 Hrs Bias @ 125°C
PCT	JESD-22-B, A102	168 Hrs, 100% RH, 121°C
TST	MIL-STD 883D-1011.9	-65°C ~ 150°C, 200 Cycles

Carrier Tape & Reel Dimensions



Carrier Tape & Reel Dimensions(Cont.)



Application	A	B	C	J	T1	T2	W	P	E
SOP-8	330±1	62 ± 1.5	12.75 + 0.15	2 + 0.5	12.4 +0.2	2± 0.2	12 + 0.3 - 0.1	8± 0.1	1.75± 0.1
	F	D	D1	Po	P1	Ao	Bo	Ko	t
	5.5 ± 0.1	1.55±0.1	1.55+ 0.25	4.0 ± 0.1	2.0 ± 0.1	6.4 ± 0.1	5.2± 0.1	2.1± 0.1	0.3±0.013

(mm)

Cover Tape Dimensions

Application	Carrier Width	Cover Tape Width	Devices Per Reel
SOP- 8	12	9.3	2500

Customer Service

Anpec Electronics Corp.

Head Office :

5F, No. 2 Li-Hsin Road, SBIP,

Hsin-Chu, Taiwan, R.O.C.

Tel : 886-3-5642000

Fax : 886-3-5642050

Taipei Branch :

7F, No. 137, Lane 235, Pac Chiao Rd.,

Hsin Tien City, Taipei Hsien, Taiwan, R. O. C.

Tel : 886-2-89191368

Fax : 886-2-89191369